DATA SHEET VOICE WARNING – (VWC)

PRODUCT CODE:	CF000636
UNICLASS:	L4231
EPIC:	D25
VERSION:	Issue H - Sent 2023







VOICE WARNING – (VWC)

PRODUCT DESCRIPTION

The Voice Warning – (VWC) offers two standard programmed messages.

Message One: "Caution, fire curtain descending" is activated during deployment of the curtain and ends when the curtain reaches its Fire Operational Position (FOP).

Message Two: "Warning, please remove obstruction" is activated when used in conjunction with the Bumper and / or Obstruction Warning optional extras.

Other / custom messages are available at request.

The Voice Warning – (VWC) is CE marked for compliance with the European Explosive Atmospheres Directive 94/9/EC and the European EMC Directive 89/336/EEC. The Voice Warning – Commercial (VWC) complies with the following standards: - EN50014: 1997

+ A1 and A2, EN50020: 2002 and EN50284: 1999.

STATUS	MESSAGE ONE	MESSAGE TWO
ALARM OK (Curtain retracted)	OFF	OFF
ALARM ACTIVATED (Curtain descending)	ON (For duration of timer. Timer set to allow curtain to fully descend)	OFF
ALARM RESET (Curtain retracting)	OFF	OFF
OBSTRUCTION DETECTED	OFF	ON

For the VWR (Voice Warning Residential) see datasheet on the website.



Input Voltage 10 – 30VDC

Sound output @ 1m 110dB(A) (Maximum)

Weight 0.75 kg

Material
UL94V0 & 5VA rated FR ABS

Colour Red (RAL3000

Dimensions (mm) 130mm(w) x 130mm(h) x 133.5mm(d)

IP Rating

Temperature Range -25°C to 55°C

Location Internal





Coopers Fire Ltd Ignis House, Houghton Avenue, Waterlooville, Hampshire PO7 3DU. United Kingdom

Phone: +44 (0)2392 454 405 Email: info@coopersfire.com Web: www.coopersfire.com Coopers Fire Ltd has a policy of continuous product improvement. As such we reserve the right to change design and specifications without prior notice.

Please check our website for the latest information

© Coopers Fire Ltd. All content and products are copyright of Coopers Fire Ltd. Registered in England Number: 2010274. Multiple patents granted and pending.