

DATA SHEET

OPTICAL SMOKE DETECTOR

PRODUCT CODE(S): 291003 (Detector)
29036 (Standard Base)
34030 (Relay Base)

UNICLASS: L4231

EPIC: D25

CI/SfB

VERSION: Issue G - Oct 2020



OPTICAL SMOKE DETECTOR

PRODUCT DESCRIPTION

Coopers Fire supply the Apollo Series 65 Optical Smoke Detector (55000-317). The Series 65 Optical Smoke Detector has a moulded self-extinguishing white polycarbonate case with wind resistant smoke inlets.

The chamber houses an infrared light emitting diode (LED) and a photo-diode which has an integral visible-light filter as extra protection against ambient light.

If light is scattered onto the photo-diode due to the presence of smoke – the detector signals an alarm state by switching the alarm latch on.

Because this is a latching device, a 'Detector Reset Switch' is required with each individual / multiple detector installation that use the Relay base.

Coopers supply all Smoke Detectors with either the standard base, which is used on MK4 and MK5 control panels or the Relay Base, which is used on System 6 PSU's and MK4-S.

SPECIFICATION

Input:
+ / - 24V DC from PSU

Output:
24V DC Alarm signal to PSU

Material:
Polycarbonate rated V-0 in accordance with UL 94.

Colour:
White

Dimensions (mm):
Detector:
100mm (dia) x 42mm (h)

Detector in Base:
100mm (dia) x 50mm (h)

Weight:
190g

IP Rating:
23D in accordance with BS EN 60529

Temperature Range:
-20°C to 60°C (no condensation or icing)

Location:
Internal

Approvals:
CE Marked
Tested and approved to EN54-7:2000



Coopers Fire Ltd
Ignis House,
Houghton Avenue,
Waterlooville, Hampshire
PO7 3DU.
United Kingdom

Phone: +44 (0)2392 454 405
Email: info@coopersfire.com
Web: www.coopersfire.com

Coopers Fire Ltd has a policy of continuous product improvement. As such we reserve the right to change design and specifications without prior notice.

Please check our website for the latest information