VS6-ERU-CAM FEATURES:

- 1 x VS6 ERU-CAM CAN CONTROL UP TO 8 MOTORS.

- TRUE GRAVITY FAILSAFE SYSTEM.

- PROVIDES BATTERY BACKUP.

- CAN BE CONFIGURED FOR MULTIPLE ALARM INPUT S/OUTPUTS.


- CAN BE CONFIGURED FOR LOCAL DETECTOR ACTIVATION - SEE DATASHEETS 'VS6-HEAT DETECTOR' OR 'VS6-SMOKE DETECTOR'.

OWS-R', 'VS6-OWS-C', 'VS6-OWS-3' OR 'VS6-OLC',

WWC'

I WC'

OVERLAPPING FIRE/SMOKE CURTAINS.



FIELD WIRING TO BE FIRE RATED IN ACCORDANCE WITH BS8519

	Ignis House, Houghton Avenue, Waterlooville, Hampshire, PO7 3DU, UK Tel: +44 (0) 23 9245 4405 Fax: +44 (0) 23 9249 2732	DRAWN	МА	TITLE	VARIOSPEED® 6 ERU-CAM TYPICAL WIRING DIAGRAM		
coopers		CHECKE D	RW	© 1997 - 2020 COOPERS FIRE LIMITED ALL RIGHTS RESERVED. THIS DESIGNMAY NOT BE REPRODUCED IN ANY MATERIAL FORM, NCLUDING ELECTRONICALLY WITHOUT THE WRITTEN PERMISSION OF THE COPYRIGHT NAMES.		ALL DMENSIONS IN MILLIMETERS UNLESS OTHERWISE STATED	
Coopers Fire Limited	Email: info@coopersfire.com		5	DRAWING		ISSUE	A
	Web: www.coopersfire.com	ersfire.com APPROVED JR NO 32001	32001	DATE	22 Jul 2020		

TABLE 1				TABLE 2							
MOTOR CABLE EXTENSION				CABLE SIZE REQUIRED FOR 'X' QTY MCU'S							
CABLE MOTOR MODEL		Q	TY MCU'S	1.5MM ²	2.5MM ²	4.0MM ²	6.0M M ²				
SIZE	11 W	30 R		1	56 M	93M	149M	22.4M			
1.5MM ²	35 M	25 M		3	22M	37M	59 M	89M			
2.5MM ²	58M	42 M		5	11 M	18M	29M	44 M			
4MM ²	93 M	67 M		8	7M	11M	18M	28M			
6MM ²	139M	100M		CA	BLE DISTAN	ICES ON A 'F	ING' SUPPL	Υ.			