## certifire

### **CERTIFICATE OF APPROVAL** No CF 10091

This is to certify that, in accordance with TS00 General Requirements for Certification of Fire Protection Products The undermentioned products of

#### **COOPERS FIRE LTD**

Ignis House, Houghton Avenue, Waterlooville, Hampshire, PO7 3DU, United Kingdom Tel: 02392 454405

> Have been assessed against the requirements of the Technical Schedule(s) denoted below and are approved for use subject to the conditions appended hereto:

CERTIFIED PRODUCT FireMaster® Insul8 – 90 Active TS 30 – Industrial Type Fire Fire Curtain

**TECHNICAL SCHEDULE Resisting Doorsets** 

Signed and sealed for and on behalf of Warringtonfire Testing and Certification Limited

Rigg

Paul Duggan **Certification Manager** 



Issued: Audit Test Frequency: Valid to:

21<sup>st</sup> February 2024 Not Applicable 20<sup>th</sup> February 2029



Page 1 of 2

This certificate is the property of Warringtonfire Testing and Certification Limited Registered in England and Wales Registered Office: 3rd Floor, Davidson Building, 5 Southampton Street, London, WC2E 7HA. Company Registration No: 11371436

# certifire

### CERTIFICATE No CF 10091 COOPERS FIRE LTD

- 1. This certification is provided to the client for their own purposes and we cannot opine on whether it will be accepted by Building Control authorities or any other third parties for any purpose.
- 2. This approval relates to the use of FireMaster® Insul8 90 Active Fire Curtain in providing a fire resistance performance of up to 90 minutes integrity and insulation, up to 240 minutes integrity only or up to 240 minutes integrity and radiation, as defined in BS EN 1634-1: 2014 + A1: 2018. This certificate is restricted to fire exposure from one direction only the curtain shall be mounted onto the opposite side of the wall to the known direction of fire exposure. The scope of approval is summarised as follows:

#### **Continuous Barriers / Single Roller**

Rating	Maximum Height (mm)	Maximum Width (mm)
Up to 90 minutes integrity and insulation	2420	7000
Up to 240 minutes integrity only	2420	7000
Up to 240 minutes integrity and radiation	2420	7000

All dimensions quoted in the above table are internally between guides and from underside of head box to floor level (i.e. visible fabric dimensions).

- 3. The product is CERTIFIRE approved on the basis of:
  - i) Initial type testing,
  - ii) An appraisal against the requirements of TS30,
  - iii) Inspection and surveillance of the Factory Production Control,
  - iv) Audit testing at a frequency as defined within TS30.
- 4. The approval relates to on-going production. The product and/or its immediate packaging is identified with the manufacturers' name, the product name or number, the CERTIFIRE name or name and mark, together with the CERTIFIRE certificate number and application where appropriate.
- 5. The FireMaster® Insul8 90 Active Fire Curtains are approved for installation on to the unexposed face of a concrete or masonry supporting construction having a fire resistance performance no less than that required for the fire curtain (see paragraph No.2, above, in regards limitation on direction of exposure). Typical installation details are provided in the datasheet.

Signed Page 2 of 2 CIH10133-1

for ligg-

Issued: 21<sup>st</sup> February 2024 Valid to: 20<sup>th</sup> February 2029